CLAIMS

What is claimed is:

1. An apparatus, comprising:

an array of tag address storage locations; and

a command sequencer and serializer unit coupled to the array of tag address

storage locations, the command sequencer and serializer unit to control a data cache

associated with a memory module.

2. The apparatus of claim 1, further comprising:

a plurality of arrays of tag address storage locations, each of the plurality of

arrays of tag address storage locations corresponding to one of a plurality of memory

modules.

3. The apparatus of claim 2, each of the plurality of arrays of tag address

storage locations organized into a plurality of ways.

4. The apparatus of claim 3, each of the plurality of arrays of tag address

storage locations organized into 4 ways.

5. The apparatus of claim 1, the command sequencer and serializer unit to

control a data cache associated with a memory module by delivering commands over a

plurality of command and address lines.

6. The apparatus of claim 5, wherein the plurality of command and address lines are part of a point-to-point interconnect.

7. An apparatus, comprising:

a memory device; and

a data cache coupled to the memory device, the data cache controlled by commands delivered by a memory controller component over a memory bus, the memory controller component including an array of tag address storage locations.

8. The apparatus of claim 7, further comprising a command decoder and deserializer unit to receive command and address information from the memory controller component, the command decoder and deserializer unit providing control for the data cache.

9. The apparatus of claim 8, wherein the data cache is organized into four ways.

10. A system, comprising:

a processor;

a memory controller coupled to the processor, the memory controller including

an array of tag address storage locations, and

a command sequencer and serializer unit coupled to the array of tag address storage locations; and

a memory module coupled to the memory controller, the memory module including

a memory device, and

a data cache coupled to the memory device, the data cache controlled by

commands delivered by the memory controller.

11. The system of claim 10, a point-to-point interconnect to couple the memory controller to the memory module.

12. The system of claim 10, the memory controller further including a plurality of arrays of tag address storage locations.

13. The system of claim 12, further comprising a plurality of memory modules, each of the plurality of memory modules including at least one of a plurality of memory devices and one of a plurality of data caches, each of the data caches controlled by commands delivered by the memory controller.

14. The system of claim 13, the plurality of arrays of tag address storage locations and the plurality of data caches organized into four ways.

15. A method, comprising:

receiving a read request at a memory controller;

performing a tag look-up within the memory controller to determine whether there is a cache hit for the read request; and

fetching a line of cache data from a data cache located on a memory module if the tag look-up indicates a cache hit.

16. The method of claim 15, further comprising:

loading a line of data from a memory device located on the memory module to the data cache if the tag look-up indicates a cache miss; and

delivering the line of data to the memory controller.